


**PCT**WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>F16D 55/40</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 98/26191</b> <b>(43) International Publication Date:</b> 18 June 1998 (18.06.98)
<b>(21) International Application Number:</b> PCT/GB97/03387 <b>(22) International Filing Date:</b> 8 December 1997 (08.12.97) <b>(30) Priority Data:</b> 9625862.9 12 December 1996 (12.12.96) GB <b>(71) Applicant (for all designated States except US):</b> T & N TECHNOLOGY LIMITED [GB/GB]; Cawston House, Cawston Lane, Rugby, Warwickshire CV22 7SA (GB). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> BUNKER, Kenneth, James [GB/GB]; 39A Mill Road, Rearsby, Leicester LE7 4YN (GB). <b>(74) Agents:</b> DRURY, Peter, Lawrence et al.; T & N plc, Bowdon House, Ashburton Road West, Trafford Park, Manchester M17 1RA (GB).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>

**(54) Title:** DISC BRAKE**(57) Abstract**

A disc brake comprises an operating mechanism (26) operable to move friction material pads (18) into contact with a disc (16). The operating mechanism comprises a support body (28) located on one side of the disc (16), a cylinder (30) defined by the support body, and a piston (32) in the cylinder. The operating mechanism also comprises a guidance member (36) for the pads (18). The guidance member (36) projects from the support body (28) past the disc (16) and supports an abutment (24) on which one of said pads (18) is mounted. The guidance member (36) is mounted on the support body (28) by means of a plurality of bolts (44) which extend through bores (48) in the guidance member to said abutment (24). The bolts (44) take the load during application of the brake.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakistan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

**DISC BRAKE**

This invention is concerned with a disc brake, for example a disc brake suitable for use in braking a wheel of a vehicle.

A conventional disc brake for a vehicle comprises a disc, friction material pads arranged on opposite sides of the disc, and an operating mechanism operable to move one of the pads into contact with the disc, and to cause relative movement between the operating mechanism and the disc to bring the other pad into contact with the disc so that the pads both apply a braking force thereto. In most cases, the disc is fixedly mounted on a hub and said relative movement is brought about by movement of the operating mechanism which is mounted so that it can slide axially of the disc. It is also possible for the operating mechanism to be fixed relative to the hub and for the disc to be slidable axially on the hub. In the latter case, there may be two or more discs slidable on the hub, and an appropriate number of pads located between the discs so that the operating mechanism can cause all the pads to contact a disc.

In a conventional disc brake as referred to above, the operating mechanism comprises a support body located on one side of the disc, a cylinder defined by the support body, and a piston in the cylinder. The piston is movable, when fluid under pressure is introduced into the cylinder, to urge a first of said pads towards the disc. The operating mechanism also comprises a guidance member projecting from the support body past the disc and supporting an abutment on which the second of said pads is mounted. Said abutment may be attached to the guidance member or may be part thereof. Said first pad is mounted for sliding movement on the guidance member.

In a conventional disc brake as referred to above, the guidance member of the operating mechanism is subject to high bending and shearing reaction forces, when the brake is applied. The bending forces result from the pressure between the pads and the disc. The shearing forces are circumferential forces and are generated by the frictional contact between the pads and the disc which are transferred to the guidance member and thence to the support body. This means that the guidance member is made from expensive high tensile material and, as it has a relatively complex shape, including accurate guidance surfaces for the brake pad, this makes the guidance member difficult and expensive to make.

The invention provides a disc brake comprising a disc, friction material pads arranged on opposite sides of the disc, and an operating mechanism operable to move one of the pads into contact with the disc, and to cause relative movement between the operating mechanism and the disc to bring the other pad into contact with the disc so that the pads both apply a braking force thereto, the operating mechanism comprising a support body located on one side of the disc, a cylinder defined by the support body, and a piston in the cylinder, the piston being movable, when fluid under pressure is introduced into the cylinder, to urge a first of said pads towards the disc, the operating mechanism also comprising a guidance member projecting from the support body past the disc and supporting an abutment on which the second of said pads is mounted, said first pad being mounted for sliding movement on the guidance member, characterised in that the guidance member of the operating mechanism is mounted on the support body thereof by means of a plurality of bolts which extend through bores in the guidance member from the support body to said abutment.

In a disc brake in accordance with the invention, the bending and shearing forces applied to the guidance member

are taken by the bolts which can be readily and cheaply obtained with the ability to take high loads so that the guidance member itself can be made from lower strength material which is cheaper and more easy to machine.

Preferably, the bolts are received in threaded bores in either the abutment or the support body. This avoids the necessity for nuts.

There now follows a detailed description, to be read with reference to the accompanying drawing, of a disc brake which is illustrative of the invention.

The drawing is an exploded view of the illustrative disc brake.

The illustrative disc brake 10 is mounted on a suspension link 12 of a vehicle. The suspension link 12 has a hub 14 mounted for rotation thereon. A wheel (not shown) is mounted on the hub in the usual manner. The brake 10 also comprises two discs 16 which are mounted on the hub 14 for axial sliding movement. Specifically, the outer surface of the hub 14 has three circumferentially-spaced surface portions which are formed with axial splines and the discs 16 are formed with teeth which mesh with these splines so that the discs can slide axially on the hub but rotate therewith. The hub 14 has three leaf springs 17 secured thereto by screws 19. The leaf springs 17 are arranged on the surface portions of the hub between the splines thereof and serve to centralise the discs 16 and to prevent them from rattling on the hub.

The brake 10 also comprises friction material pads 18 arranged on opposite sides of each of the discs 16. Specifically, one of the friction pads 18 is mounted on a backing plate 20 on one side of a first of the discs 16, two of the pads 18 are mounted on opposite sides of a

backing plate 22 which is between the first and the second discs 16, and one of the pads 18 is mounted on an abutment 24 on an opposite side of the second disc 16 to the backing plate 22.

The brake 10 also comprises an operating mechanism 26 operable to move the pad 18 on the backing plate 20 into contact with the first disc 16. The mechanism 26 is also affective to cause relative movement between the mechanism 26 and the discs 16 to bring the other pads 18 mounted on the backing plate 22 and the abutment 24 into contact with the discs so that the pads all apply a braking force to the discs. Specifically, movement of the pad 18 on the backing plate 20 into contact with the first disc 16 causes the first disc 16 to slide on the hub 14 into contact with one of the pads 18 on the backing plate 22, continued movement brings the other pad 18 on the backing plate 22 into contact with the second disc 16 which, in turn, slides on the hub 14 until the second disc 16 contacts the pad 18 on the abutment 24.

The operating mechanism 26 comprises a support body 28 which is located on one side of the first disc 16. The support body 28 is provided by a portion of the link 12. The operating mechanism 26 also comprises a cylinder 30 defined by the support body 28, and a piston 32 in the cylinder. The piston 32 is movable, when fluid under pressure is introduced into the cylinder 30 through a port 34 to move out of the cylinder and thereby urge the backing plate 20 and the pad 18 mounted thereon towards the first disc 18.

The operating mechanism 26 also comprises a guidance member 36 projecting from the support body 28 past the discs 16. The guidance member 36 supports the abutment 24. The backing plates 20 and 22 and the pads mounted thereon are mounted for sliding movement on the guidance member 36.

Specifically, the guidance member 36 has two arcuate side surfaces 38 on which the plates 20 and 22 slide. The plates 20 and 22 having upper hook portions 40 which hook over the surfaces 38 so that the plates 20 and 22 are supported by the member 36 and can slide along the member 36. A leaf spring 42 is provided between the underside of the member 36 and the plates 20 and 22, the spring 42 serving to prevent rattling.

The guidance member 36 of the operating mechanism 26 is mounted on the support body 28 by means of a two high tensile bolts 44 which pass through bores 46 in the support body 28 and bores 48 in the guidance member 36 to enter threaded bores 50 in the abutment 24.


In the operating mechanism 26, introduction of hydraulic fluid under pressure into the cylinder 30 causes the piston 32 to urge the pads 18 into contact with the discs 16 as aforementioned. When this contact has been achieved braking forces between each of the pads 18 and the discs 16 are transmitted to the member 36 via the backing plates 20 and 22 and the abutment 24. However, the high bending and shearing forces applied thereby to the guidance member 36 is taken by the bolts 44.

## CLAIMS

- 1 A disc brake (10) comprising a disc (16), friction material pads (18) arranged on opposite sides of the disc, and an operating mechanism (26) operable to move one of the pads into contact with the disc, and to cause relative movement between the operating mechanism and the disc to bring the other pad into contact with the disc so that the pads both apply a braking force thereto, the operating mechanism comprising a support body (28) located on one side of the disc (16), a cylinder (30) defined by the support body, and a piston (32) in the cylinder, the piston being movable, when fluid under pressure is introduced into the cylinder, to urge a first of said pads (18) towards the disc (16), the operating mechanism (26) also comprising a guidance member (36) projecting from the support body (28) past the disc (16) and supporting an abutment (24) on which the second of said pads (18) is mounted, said first pad (18) being mounted for sliding movement on the guidance member (36), characterised in that the guidance member (36) of the operating mechanism (26) is mounted on the support body (28) thereof by means of a plurality of bolts (44) which extend through bores (48) in the guidance member (36) from the support body (28) to said abutment (24).
- 2 A disc brake according to claim 1, characterised in that the bolts (44) are received in threaded bores (50) in either the abutment (24) or the support body (28).



1/1



# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 97/03387

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 F16D55/40

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 F16D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2 943 827 A (E.H.HARTEL ET AL) 5 July 1960 see figure 2 see column 2, line 43 - column 3, line 2 ---	1,2
Y	WO 89 05924 A (ALLIED SIGNAL INC) 29 June 1989 see figures 1,2 see page 10, line 21 - page 13, line 29 ---	1,2
Y	PATENT ABSTRACTS OF JAPAN vol. 006, no. 172 (M-154), 7 September 1982 & JP 57 083733 A (AKEBONO BRAKE IND CO LTD), 25 May 1982, see abstract; figures --- -/--	1,2

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

24 March 1998

Date of mailing of the international search report

30/03/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Westland, P

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 97/03387

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 208 559 A (CHAMBERS ET AL) 28 September 1965 see figure see column 2, line 12 - line 34 see column 2, line 44 - line 55 ---	1
A	US 3 494 448 A (RUPRECHT ROBERT ET AL) 10 February 1970 see claims 1-3; figure see column 1, line 31 - line 70 see column 2, line 38 - column 3, line 12 ---	1,2
A	US 5 472 068 A (WEILER ROLF ET AL) 5 December 1995 see abstract; claims 1,2; figures 1,2 see column 1, line 7 - column 2, line 14 see column 4, line 13 - line 33 ---	1,2
A	DE 27 39 128 A (KLOECKNER HUMBOLDT DEUTZ AG) 15 March 1979 see figures see page 3, line 18 - page 4, line 21 -----	1

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 97/03387

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2943827 A	05-07-60	NONE	
WO 8905924 A	29-06-89	US 4844206 A CA 1314499 A CN 1037761 A,B DE 3875977 A EP 0394337 A JP 4503239 T US 4865160 A	04-07-89 16-03-93 06-12-89 17-12-92 31-10-90 11-06-92 12-09-89
US 3208559 A	28-09-65	NONE	
US 3494448 A	10-02-70	FR 1548334 A GB 1161355 A	06-12-68 13-08-69
US 5472068 A	05-12-95	DE 4202394 A DE 59204005 D WO 9217712 A EP 0577671 A	08-10-92 16-11-95 15-10-92 12-01-94
DE 2739128 A	15-03-79	NONE	